YUA

Fast · Accurate · Managing

Ultra-fast
response time

Outstanding
Long-term Stability

Fixinst-A Patented Al2O3
Sensor Technology



F108x Series
Dewpoint Meter

FIXINST-A New-generation Al_2O_3 Standard Dewpoint Transmitter

DEWPOINT METER

Product Overview

When the dewpoint of the measuring medium is below -40 °Ctd, the aluminum oxide sensor is the most accurate, responsive and long-term stable in comparison with other types of sensors. Meanwhile, it has excellent anti-pollution ability

Revolutionary auto-calibration circuit design automatically compen sates for circuit drift caused by temperature, contamination, and aging, providing long-term stability and high accuracy measurements

Innovative temperature compensation algorithm and multi-point temperature compensation calibration, greatly improving the sensor's temperature drift and ensuring high-precision dew point measurement over a wide temperature range

Product Advantages

Innovative Sensor Tech

Low dewpoint, high humidity resistance, long-term stability

Excellent anti-pollution ability

Anti-Condensation,
Anti-Particle Contamination

Ultra-wide Range

-100 … +20 °Ctd

Self-calibration circuit


Provides measurement accuracy and stability

Fast Response Time

Dewpoint can be down to -70 °Ctd or lower within 30 min

- FixInst new generation ultra-fast response aluminum oxide sensor technology
- Application in dewpoint < -60 °Ctd:
  Cold dryers, suction dryers, industrial gases
- 10+ points of dew point calibration and multi-point temperature compensation provide accurate measurements up to ±2 °Ctd (Refer to “Technical Data”)
- Ultra-fast response time and outstanding long-term stability
- Anti-condensation, resistant to particulate contamination, oil vapor and most chemicals
- Excellent immunity to interference
- IP65 protection class, providing good protection even in harsh environments
- Provides comprehensive sensor setup, data transfer, software upgrades, and maintenance via Modbus RTU (RS485) interface and powerful service APP
- Calibration is valid for two years, reducing maintenance

Product Dimensions



Sensor Model	FixInst-P	FIXINST-A	FIXINST-Q
Sensor Type	Polymer Capacitive Sensors	Aluminum Oxide Sensors	QCM Sensor
Sensor View			
Application in > -60 °Ctd: Refrigerant Dryer, Desiccant Dryer, Industrial Gas	✓		
Application in -80 … -60 °Ctd: Desiccant Dryer, Nitrogen Generators, Industrial Gas		✓	
Application in -120 … -80 °Ctd: High-purity industrial gas		○	✓
Containing contaminated particles	✓	✓	

* Sensor FIXINST-A FIXINST-Q have obtained relevant patents

○ Model F139C-Puri, F305B

Product Applications

Dew point meters are widely used in dry purification, chemical, petrochemical, power engineering, and food & medicine etc.



Gas monitoring of drying equipment

* Refrigeration Dryer Desiccant dryer Membrane dryer



Vessel and pipeline gas monitoring




Medical and surgical gas monitoring



Moisture monitoring of industrial gases



Monitoring of dry and clean environments



Dryness test for food and drug additives

Technical Data

Measurement Range

Dewpoint	
F108A	-80 … +20 °Ctd
F108B	-110 … +20 °Ctd
Temperature	-40 … +100 °C

Accuracy

Dewpoint (Air or Nitrogen)	
+20… -60 °Ctd	±2 °Ctd
-60 … -100 °Ctd	±3 °Ctd
Temperature (Customizable)	
0 … +50 °C	± 0.3 °C (Standard)
-40 … 0 °C & +50 … +100 °C	± 0.5 °C (Standard)

Response Time

Dewpoint: 63% [90%], Reference: 20 °C, 1bar(a), 4L/min

-50 →+20 °Ctd	20 sec [40 sec]
+20 → -50 °Ctd	1 min [3 min]

Power

Measuring State	10 … 30VDC	Max 1.5W @ 24VDC

Output

Analog Output (Customized)	4 … 20 mA (3-wire)
Analog Resolution	0.002 mA
Analog Drift	0.01 % of span/°C
Digital Output	Max. 500 ohm
Digital Output	Modbus RTU (RS485)
Connector	5pin M8, Female

Operating Environment

Operating Temperature	-30 … +70 °C
Storage Temperature	-40 … +80 °C
Relative Humidity	0 … 95 %RH
Sample Gas Flow Rate	> 1 L/min
Pressure	0 … 5 MPa(a) 0 … 35 MPa(a) (Option)

Other

Process Connection	ISO G1/2″ thread (Standard) 3/4″ - 16 UNF thread (Customized) 5/8" - 18 UNF thread (Customized)
Protection Code	IP65
Housing Material	SUS304
Sensor Filter	Stainless steel mesh filter (Filtration class 70 um)
EMC	Compliant with IEC 61326-1

Order Information

Model	Digital Output	Analog Output	Sensor Filter	Cable / Connector	Analog Output Unit	Pressure	Withstand Pressure	Description
F108A								-80 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, G1/2" thread
F108A-U1								-80 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, 3/4" -16 UNF thread
F108A-U2								-80 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, 5/8" -18 UNF thread
F108B								-110 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, G1/2" thread
F108B-U1								-110 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, 3/4" -16 UNF thread
F108B-U2								-110 … +20 °Ctd, Al2O3 sensor, Standard stainless steel housing, 5/8" -18 UNF thread
	1							Modbus RTU (RS485)
		1						4 … 20 mA
			S0301 0005					Stainless steel mesh filter (Filtration class 70 um, Default)
				M2701 0004				M12 female straight connectors, IP67, With 2m cable (Default)
					V0101 0001			Default output unit
					V0101 0002			Output unit (Customized)
						V0103 0001		Defualt 0 bar(g)
						V0103 0002		Customized
							V0103 0003	Maximum operating pressure: 0 … 35 MPa(a)
							V0103 0004	Maximum operating pressure: 0 … 5 MPa(a)

* Wi-SUN wireless is available as an option. Please consult sales staff for details

* For other accessories please refer to **YUA Instruments** Product Catalog or consult sales